

Safety Data Sheet

Issue Date: 02-Feb-2015	Revision Date: 03-Mar-2015	Version 1	
	1. IDENTIFICATION		
<u>Product Identifier</u> Product Name	ArmorCoat™ Clear Spray-On Paint Protect	ion Bra AC-2B	
Other means of identification SDS #	AA-05		
UN/ID No	UN1993		
<u>Recommended use of the chemic</u> Recommended Use	Recommended use of the chemical and restrictions on use Recommended Use Paint protection.		
Details of the supplier of the safet Supplier Address Armor Auto LLC P.O. Box 3974 Missoula, MT 59806	ty data sheet		
Emergency Telephone Number Company Phone Number Emergency Telephone (24 hr)	1-800-433-6903 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)		
	2. HAZARDS IDENTIFICATIO	DN	
Appearance Clear liquid	Physical State Liquid	Odor Solvent	
Classification_			
Serious eye damage/eye irritation Specific target organ toxicity (single Flammable Liquids	exposure)	Category 2 Category 3 Category 2	

<u>Signal Word</u> Danger

Hazard Statements

Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Acetone	67-64-1	20-25
1-chloro-4(trifluoromethyl) benzene	98-56-6	15-25
Ethyl 3-ethoxypropionate	763-69-9	<5
n-Butyl acetate	123-86-4	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately.
Ingestion	Rinse mouth. Do not induce vomiting. Get medical attention to assess further treatment.
Most important symptoms and effe	<u>cts</u>
Symptoms	Causes serious eye irritation. Exposed individuals may experience eye tearing, redness and discomfort. May cause irritation, redness and pain. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. Drowsiness. Asthmatic type symptoms may develop immediately or after several hours. Ingestion may cause nausea, vomiting and abdominal pain.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Water may be used to cool closed containers to prevent pressure buildups and possible ignition or explosion when exposed to extreme heat. Vapors are heavier than air and may travel along ground to ignition sources and flash back.

Hazardous Combustion Products Toxic gases may be formed by fire. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge. Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Ventilate affected area.
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment	Absorb spill with inert material (e.g. dry sand or earth).
Methods for Clean-Up	Keep in suitable, closed containers for disposal. Use non-sparking hand tools and explosion-proof electrical equipment. Clean up in accordance with all applicable regulations.

7. HANDLING AND STORAGE

Precautions for safe handling	
Advice on Safe Handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground container and transfer equipment to eliminate static electric sparks. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges.
Conditions for safe storage, includi	ing any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from heat, sparks, flame.
Incompatible Materials	Strong oxidizing agents. Water. Bases. Alcohols. Amines.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	-
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors	
		(vacated) STEL: 1000 ppm	
1-chloro-4(trifluoromethyl) benzene	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F	-
98-56-6		TWA: 2.5 mg/m ³ dust	
		(vacated) TWA: 2.5 mg/m ³	
n-Butyl acetate	STEL: 200 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 150 ppm	TWA: 710 mg/m ³	TWA: 150 ppm
		(vacated) TWA: 150 ppm	TWA: 710 mg/m ³
		(vacated) TWA: 710 mg/m ³	STEL: 200 ppm
		(vacated) STEL: 200 ppm	STEL: 950 mg/m ³
		(vacated) STEL: 950 mg/m ³	

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear approved safety goggles.
Skin and Body Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2).

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Appearance Color	Liquid Clear liquid Clear	Odor Odor Threshold	Solvent Not determined
Property pH Melting Point/Freezing Point Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit Vapor Pressure Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition Coefficient Auto-ignition Temperature Decomposition Temperature Kinematic Viscosity Dynamic Viscosity Explosive Properties	Values Not determined Not available 67-138 °C / 153-282 °F 1.6 °C / 35 °F Slower than ether Liquid-not applicable Not determined Not determined	Remarks • Method Tag Closed Cup	Not determined
Oxidizing Properties VOC Content Density	Not determined 2.08 lbs non-exempt solvent per adju 8.71 lb/gal	isted gallon	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization may occur.

Conditions to Avoid

See Sec. 7 Handling & Storage.

Incompatible Materials

Strong oxidizing agents. Water. Bases. Alcohols. Amines.

Hazardous Decomposition Products

Toxic gases may be formed by fire. Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Eye Contact	Causes serious eye irritation.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	-
1-chloro-4(trifluoromethyl) benzene 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat)4 h
Propylene glycol monomethyl ether acetate 108-65-6	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Ethyl 3-ethoxypropionate 763-69-9	= 3200 mg/kg (Rat)	= 10 mL/kg (Rabbit)	-
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 391 ppm (Rat)4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
STOT - single exposure	May cause drowsiness or dizziness.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Acetone		4.74 - 6.33: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia
67-64-1		Oncorhynchus mykiss mL/L		magna mg/L EC50 Static
		LC50 6210 - 8120: 96 h		12600 - 12700: 48 h Daphnia
		Pimephales promelas mg/L		magna mg/L EC50
		LC50 static 8300: 96 h		
		Lepomis macrochirus mg/L		
		LC50		
1-chloro-4(trifluoromethyl)		11.5 - 15.8: 48 h Lepomis		3.68: 48 h Daphnia magna
benzene		macrochirus mg/L LC50		mg/L EC50
98-56-6		static		_
Propylene glycol		161: 96 h Pimephales		500: 48 h Daphnia magna
monomethyl ether acetate		promelas mg/L LC50 static		mg/L EC50
108-65-6				
Ethyl 3-ethoxypropionate		62: 96 h Pimephales		970: 48 h Daphnia magna
763-69-9		promelas mg/L LC50 static		mg/L EC50
n-Butyl acetate	674.7: 72 h Desmodesmus	17 - 19: 96 h Pimephales	EC50 = 70.0 mg/L 5 min	72.8: 24 h Daphnia magna
123-86-4	subspicatus mg/L EC50	promelas mg/L LC50	EC50 = 82.2 mg/L 15 min	mg/L EC50
		flow-through 100: 96 h	EC50 = 959 mg/L 18 h	_
		Lepomis macrochirus mg/L	EC50 = 98.9 mg/L 30 min	
		LC50 static 62: 96 h	-	
		Leuciscus idus mg/L LC50		
		static		

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

<u>Mobility</u>

Chemical Name	Partition Coefficient
Acetone	-0.24
67-64-1	
1-chloro-4(trifluoromethyl) benzene	3.7
98-56-6	
Propylene glycol monomethyl ether acetate	0.43
108-65-6	
Ethyl 3-ethoxypropionate	1.35
763-69-9	
n-Butyl acetate	1.81
123-86-4	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
n-Butyl acetate 123-86-4	Toxic

14. TRANSPORT INFORMATION

Note_	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
DOT UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1993 Flammable liquids, n.o.s. (acetone, 1-chloro-4(trifluoromethyl) benzene)) 3 II
IATA UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1993 Flammable liquids, n.o.s. (acetone, 1-chloro-4(trifluoromethyl) benzene)) 3 II
IMDG UN/ID No Proper Shipping Name Hazard Class Packing Group Marine Pollutant	UN1993 Flammable liquids, n.o.s. (acetone, 1-chloro-4(trifluoromethyl) benzene)) 3 II This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Acetone	Present	Х		Present		Present	Х	Present	Х	Х
1-chloro-4(trifluoromethyl) benzene	Present	Х		Present		Present	Х	Present	Х	Х
Ethyl 3-ethoxypropionate	Present	Х		Present		Present	Х	Present	Х	Х
n-Butyl acetate	Present	Х		Present		Present	Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>CERCLA</u>

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ
123-86-4			RQ 2270 kg final RQ

SARA 313

Not determined

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			Х

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone	Х	Х	Х
67-64-1			
1-chloro-4(trifluoromethyl) benzene	Х		Х
98-56-6			
n-Butyl acetate	Х	Х	Х
123-86-4			

16. OTHER INFORMATION

<u>NFPA</u> HMIS	Health Hazards Not determined Health Hazards 3	Flammability Not determined Flammability 3	Instability Not determined Physical Hazards 1	Special Hazards Not determined Personal Protection H
Issue Date: Revision Date: Revision Note:	02-Feb-20 03-Mar-20 New form	015		

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet